

In the Claims:

Please amend the claims as follows:

1. (Currently Amended) An image decoder, comprising:
a memory having rows of storage locations; and
a processor coupled to the memory and operable to,
store ~~a column of intermediate values in a row of the memory~~ intermediate values from first and second matrix columns as a row of intermediate values,
combine the stored intermediate values within the ~~stored~~ row to generate a column of resulting values for third and fourth matrix columns, and
store the resulting values in respective rows of the memory ~~as a row of resulting values~~.

AB 2. (Original) The image decoder of claim 1 wherein the intermediate values comprise Masaki values.

3. (Currently amended) The image ~~processing circuit~~ decoder of claim 1, wherein:
the memory comprises first and second rows of storage locations; and
the processor is operable to,
store the intermediate values in the first row of storage locations, and
store the resulting values in the second row of storage locations.

4. (Currently amended) The image ~~processing circuit~~ decoder of claim 1 wherein the processor is operable to generate the ~~column of intermediate values~~ from the first matrix column.

5. (Currently amended) An image decoder, comprising:
a memory;
a processor coupled to the memory and operable to,

store a column of intermediate values in the memory as a row of intermediate values,

combine the intermediate values within the stored row to generate a column of resulting values, and

store the resulting values in the memory as a row of resulting values;~~The image decoder of claim 1~~

wherein the intermediate values comprise an even-position even intermediate value, an odd-position even intermediate value, an even-position odd intermediate value, and an odd-position odd intermediate value;

wherein the row has storage locations; and

wherein the processor is operable to store,

the even-position even intermediate value and the even-position odd intermediate value in respective adjacent storage locations, and

the odd-position even intermediate value and the odd-position odd intermediate value in respective adjacent storage locations.

6. (Currently amended) An image decoder, comprising:
a memory;

a processor coupled to the memory and operable to,

store a column of intermediate values in the memory as a row of intermediate values,

combine the intermediate values within the stored row to generate a column of resulting values, and

store the resulting values in the memory as a row of resulting values;~~The image decoder of claim 1~~

wherein the intermediate values comprise an even-position even intermediate value, an odd-position even intermediate value, an even-position odd intermediate value, and an odd-position odd intermediate value;

wherein the row has storage locations; and

wherein the processor is operable to store,

the even-position even intermediate value and the even-position odd intermediate value in a first pair of adjacent storage locations, and

the odd-position even intermediate value and the odd-position odd intermediate value in a second pair of adjacent storage locations, the second pair of storage locations being adjacent to the first pair of adjacent storage locations.

7. (Currently amended) An image decoder, comprising:
a memory;

a processor coupled to the memory and operable to,

store a column of intermediate values in the memory as a row of intermediate values,

combine the intermediate values within the stored row to generate a column of resulting values, and

store the resulting values in the memory as a row of resulting values;The image decoder of claim 1

wherein: the intermediate values comprise a first even-position even intermediate value, an odd-position even intermediate value, a second even-position even intermediate value, a first even-position odd intermediate value, an odd-position odd intermediate value, and a second even-position odd intermediate value;

wherein the row has storage locations; and

wherein the processor is operable to store,

the first even-position even intermediate value and the first even-position odd intermediate value in a first pair of adjacent storage locations,

the second even-position even intermediate value and the second even-position odd intermediate value in a second pair of adjacent storage locations, the second pair of storage locations being adjacent to the first pair of storage locations, and

the odd-position even intermediate value and the odd-position odd intermediate value in a third pair of adjacent storage locations.

8. (Original) The image decoder of claim 1 wherein the resulting values comprise respective partial inverse-transform values.

9. (Currently amended) An image decoder, comprising:
~~a first-memory rows register; and~~
a processor coupled to the memory register~~rows~~ and operable to,
combine a first matrix column of first intermediate values with a second matrix
column of second intermediate values to generate a set of resulting values; and
store the set of resulting values in more than one of the first-memory
register~~rows~~.

10. (Original) The image decoder of claim 9 wherein:
the first intermediate values comprise even Masaki values; and
the second intermediate values comprise odd Masaki values.

11. (Currently amended) The image ~~processing circuit~~decoder of claim 9, ~~further~~
comprising:
~~a second-memory register; and~~
wherein the processor is further operable to store the first and second intermediate
values of the first and second matrix columns in more than one of the second-memory
row~~registers~~.

12. (Currently amended) The image ~~processing circuit~~decoder of claim 9 wherein
the processor is operable to combine the first column of first intermediate values with the
second column of second intermediate values by adding the first intermediate values to the
second intermediate values.

13. (Currently amended) The image ~~processing circuit~~decoder of claim 9 wherein
the processor is operable to combine the first matrix column of first intermediate values
with the second matrix column of second intermediate values by subtracting the first
intermediate values from the second intermediate values.

14. (Currently amended) The image ~~processing circuit~~decoder of claim 9 wherein
the processor is operable to generate the first matrix column of first intermediate values
and the second matrix column of second intermediate values.

15. (Original) An image decoder, comprising:

first and second memory registers having respective storage locations; and
a processor coupled to the registers and operable to,

store each of a set of first intermediate values in every other respective
storage location of the first memory register, the set of first intermediate values
corresponding to a set of initial values,

store each of a set of second intermediate values in remaining storage
locations of the first memory register, the set of second intermediate values
corresponding to the set of initial values,

combine each first intermediate value with a second intermediate value that
occupies a respective adjacent storage location to generate respective resulting
values; and

store each of the resulting values in a respective storage location of the
second memory register.

16. (Original) The image decoder of claim 15 wherein:

the first intermediate values comprise even Masaki values; and
the second intermediate values comprise odd Masaki values.

17. (Original) The image decoder of claim 15 wherein the set of initial values
comprises a block of discrete-cosine-transform coefficients.

18. (Original) The image decoder of claim 15 wherein:

the set of first intermediate values corresponds to a first subset of the set of initial
values; and

the set of second intermediate values corresponds to a second subset of the set of
initial values.

19. (Original) The image decoder of claim 15 wherein:

the set of initial values comprises rows of discrete-cosine-transform coefficients;

each of the first intermediate values corresponds to the discrete-cosine-transform coefficients that occupy even locations of a respective row; and

each of the second intermediate values corresponds to the discrete-cosine-transform coefficients that occupy odd locations of the respective row.

20. (Original) The image decoder of claim 15 wherein:

the set of initial values comprises rows of discrete-cosine-transform coefficients, each row having respective even and odd locations;

the processor is operable to generate each of the first intermediate values from the discrete-cosine-transform coefficients that occupy even locations of a respective row; and

the processor is operable to generate each of the second intermediate values from the discrete-cosine-transform coefficients that occupy odd locations of the respective row.

AS
cont
21. (Currently amended) The image ~~processing circuit~~decoder of claim 15 wherein the processor is operable to combine each first intermediate value with a second intermediate value by adding each first intermediate value to the second intermediate value that occupies the respective adjacent storage location.

22. (Currently amended) The image ~~processing circuit~~decoder of claim 15 wherein the processor is operable to combine each first intermediate value with a second intermediate value by subtracting each first intermediate value from the second intermediate value that occupies the respective adjacent storage location.

23. (Currently amended) The image ~~processing circuit~~decoder of claim 15 wherein the processor is operable to:

store each of the set of first intermediate values by storing first and second ones of the first intermediate values in first and third storage locations, respectively, of the first memory register;

store each of the set of second intermediate values by storing first and second ones of the second intermediate values in second and fourth storage locations, respectively, of the first memory register;

combine each first intermediate value with a second intermediate value by combining the first and second ones of the first intermediate values with the first and second ones, respectively, of the second intermediate values to generate respective first and second resulting values; and

store each of the resulting values by storing the first and second resulting values in first and second locations, respectively, of the second memory register.

24. (Currently amended) The image ~~processing circuit~~decoder of claim 15 wherein the processor is operable to:

store each of the set of first intermediate values by storing first and third ones of the first intermediate values in first and third storage locations, respectively, of the first memory register;

store each of the set of second intermediate values by storing first and third ones of the second intermediate values in second and fourth storage locations, respectively, of the first memory register;

combine each first intermediate value with a second intermediate value by combining the first and third ones of the first intermediate values with the first and third ones, respectively, of the second intermediate values to generate respective first and second resulting values; and

store each of the resulting values by storing the first and second resulting values in first and second locations, respectively, of the second memory register.

25. (Original) An image decoder, comprising:
a processor operable to:

receive pixel values that each occupy a respective position within an original row of pixel values,

store the pixel values that respectively occupy every other position of the row in a first continuous section of a register, and

store the pixel values that respectively occupy remaining positions of the row in a second continuous section of the register.

26. (Currently amended) The image decoder of claim 24-25 wherein:
the every other row positions comprise even positions within the row; and
the remaining positions comprise odd positions within the row.

27. (Currently amended) The image decoder of claim 24-25 wherein the pixel
values each comprise a respective encoded pixel value.

28. (Currently amended) The image decoder of claim 24-25 wherein the pixel
values each comprise a respective discrete-cosine-transform coefficient.

29. (Currently amended) The image decoder of claim 24-25 wherein the
processor is further operable to receive a block of pixel values, the block including the row
of pixel values, the pixel values being arranged in a zigzag pattern.

30. (Currently amended) A method, comprising:
storing in a row of a memory ~~a column of~~ intermediate values from first and
second matrix columns ~~as a row of intermediate values~~;
generating ~~a column of~~ resulting values for third and fourth matrix columns by
combining the stored intermediate values within the ~~stored~~ row; and
storing the resulting values in respective rows of the memory ~~as a row of resulting~~
values.

31. (Original) The method -of claim 30 wherein the intermediate values comprise
Masaki values.

32. (Canceled)

33. (Currently amended) The method of claim 30, further comprising generating
the first and second matrix columns of intermediate values.

34. (Currently amended) A method, comprising:
storing a column of intermediate values as a row of intermediate values;

generating a column of resulting values by combining the intermediate values within the stored row;

storing the resulting values as a row of resulting values;~~The method of claim 30~~

wherein: the intermediate values include an even-position even intermediate value, an odd-position even intermediate value, an even-position odd intermediate value, and an odd-position odd intermediate value; and

wherein the storing the column of intermediate values comprises,

storing the even-position even intermediate value and the even-position odd intermediate value in respective adjacent storage locations of a row, and

storing the odd-position even intermediate value and the odd-position odd intermediate value in other respective adjacent storage locations of the row.

35. (Currently amended) A method, comprising:

storing a column of intermediate values as a row of intermediate values;

generating a column of resulting values by combining the intermediate values within the stored row;

storing the resulting values as a row of resulting values;~~The method of claim 30~~

wherein: the intermediate values include an even-position even intermediate value, an odd-position even intermediate value, an even-position odd intermediate value, and an odd-position odd intermediate value; and

wherein the storing the column of intermediate values comprises:

storing the even-position even intermediate value and the even-position odd intermediate value in a first pair of adjacent storage locations, and

~~and~~ storing the odd-position even intermediate value and the odd-position odd intermediate value in a second pair of adjacent storage locations, the second pair of storage locations being adjacent to the first pair of adjacent storage locations.

36. (Currently amended) A method, comprising:

storing a column of intermediate values as a row of intermediate values;

generating a column of resulting values by combining the intermediate values within the stored row;

storing the resulting values as a row of resulting values~~The image decoder method of claim 30~~

wherein the intermediate values include a first even-position even intermediate value, an odd-position even intermediate value, a second even-position even intermediate value, a first even-position odd intermediate value, an odd-position odd intermediate value, and a second even-position odd intermediate value; and

wherein the storing the column of intermediate values comprises,

storing the first even-position even intermediate value and the first even-position odd intermediate value in a first pair of adjacent storage locations,

storing the second even-position even intermediate value and the second even-position odd intermediate value in a second pair of adjacent storage locations, the second pair of storage locations being adjacent to the first pair of storage locations, and

storing the odd-position even intermediate value and the odd-position odd intermediate value in a third pair of adjacent storage locations.

37. (Currently amended) A method, comprising:

combining a first matrix column of first intermediate values with a second matrix column of second intermediate values to generate a set of resulting values; and

storing the set of resulting values in more than one row of a first-memory register.

38. (Original) The method of claim 37 wherein:

the first intermediate values comprise even Masaki values; and
the second intermediate values comprise odd Masaki values.

39. (Currently amended) The method of claim 37, further comprising storing the first and second intermediate values of the first and second matrix columns in more than one row of the~~a second memory register~~.

40. (Currently amended) The method of claim 37 ~~image processing circuit of claim 1~~ wherein the combining comprises adding the first intermediate values to the second intermediate values.

41. (Original) The method of claim 37 wherein the combining comprises subtracting the first intermediate values from the second intermediate values.

42. (Currently amended) The method of claim 37, further comprising:
generating the first matrix column of first intermediate values; and
generating the second matrix column of second intermediate values,

AB
CD
43. (Original) A method, comprising:
storing each of a set of first intermediate values in every other respective storage location of a first memory register, the set of first intermediate values corresponding to a set of initial values;
storing each of a set of second intermediate values in remaining storage locations of the first memory register, the set of second intermediate values corresponding to the set of initial values;
generating respective resulting values by combining each first intermediate value with a second intermediate value that occupies a respective adjacent storage location of the first memory register; and
storing each of the resulting values in a respective storage location of a second memory register.

44. (Original) The method of claim 43 wherein:
the first intermediate values comprise even Masaki values; and
the second intermediate values comprise odd Masaki values.

45. (Original) The method of claim 43 wherein the set of initial values comprises a block of discrete-cosine-transform coefficients.

46. (Original) The method of claim 43 wherein:
the set of first intermediate values corresponds to a first subset of the set of initial values; and
the set of second intermediate values corresponds to a second subset of the set of initial values.

47. (Original) The method of claim 43 wherein:
the set of initial values comprises rows of discrete-cosine-transform coefficients;
each of the first intermediate values corresponds to the discrete-cosine-transform coefficients that occupy even locations of a respective row; and
each of the second intermediate values corresponds to the discrete-cosine-transform coefficients that occupy odd locations of the respective row.

48. (Original) The method of claim 43, further comprising:
wherein the set of initial values comprises rows of discrete-cosine-transform coefficients, each row having respective even and odd locations;
generating each of the first intermediate values from the discrete-cosine-transform coefficients that occupy even locations of a respective row; and
generating each of the second intermediate values from the discrete-cosine-transform coefficients that occupy odd locations of the respective row.

49. (Original) The method of claim 43 wherein the generating comprises adding each first intermediate value to the second intermediate value that occupies the respective adjacent storage location of the first memory register.

50. (Original) The method of claim 43 wherein the generating comprises subtracting each first intermediate value from the second intermediate value that occupies the respective adjacent storage location of the first memory register.

51. (Original) The method of claim 43 wherein:

the storing the first intermediate values comprises storing first and second ones of the first intermediate values in first and third storage locations, respectively, of the first memory register;

the storing the second intermediate values comprises storing first and second ones of the second intermediate values in second and fourth storage locations, respectively, of the first memory register;

the generating comprises combining the first and second ones of the first intermediate values with the first and second ones, respectively, of the second intermediate values to generate respective first and second resulting values; and

the storing the resulting values comprises storing the first and second resulting values in first and second locations, respectively, of the second memory register.

AD
CDL
52. (Original) The method of claim 43 wherein:

the storing the first intermediate values comprises storing first and third ones of the first intermediate values in first and third storage locations, respectively, of the first memory register;

the storing the second intermediate values comprises storing first and third ones of the second intermediate values in second and fourth storage locations, respectively, of the first memory register;

the generating comprises combining the first and third ones of the first intermediate values with the first and third ones, respectively, of the second intermediate values to generate respective first and second resulting values; and

the storing the resulting values comprises storing the first and second resulting values in first and second locations, respectively, of the second memory register.

53. (Original) A method, comprising:

storing the pixel values that respectively occupy every other position of a row of pixel values in a first continuous section of a register; and

storing the pixel values that respectively occupy remaining positions of the row in a second continuous section of the register.

54. (Original) The method of claim 53 wherein:
the every other row positions comprise even positions within the row; and
the remaining positions comprise odd positions within the row.

55. (Original) The method of claim 53 wherein the pixel values each comprise a
respective encoded pixel value.

AD
CD's 56. (Original) The method of claim 53 wherein the pixel values each comprise a
respective discrete-cosine-transform coefficient.

57. (Original) The method of claim 53, further comprising extracting the row of
pixel values from a zigzag-encoded block of pixel values.
